

PARQUET FLOORING

ASH 14MM RUSTIC WHITE, 3 STRIP, 5G[®], MATT



EAN	5710764671273
ART.nr	9752596
Surface material	Ash
Surface treatment	Matt Lacquer
Stained	White
Design features	No
Grading	Rustic
Locking system	5G [®]
Material Core/Back	Pine / Spruce / Alder
Board thickness (mm)	14
Board surface length (mm)	2423
Board surface width (mm)	200
Wear layer thickness (mm)	3,5
Re-sandable	Yes
Strips	3
Boards per package	8 pcs
Square meters per package	2,91 m ²
Wight per m ² (kg)	7,51 kg
Weight per package (kg)	22 kg
Nordic Swan Ecolabel	Yes
Made in	EU
Brinell Value	4
Suitable with Floor heating	Yes: Max 27°C and 80W / m ²
Package info	May contain start/stop boards
Moisture content (EN13183)	7% ±2%
Minimum Mean Density kg/m ³	>500 kg / m ³
Reaction to Fire (EN1350-1)	Dfl-s1
Formaldehyde Emission (EN717-1)	E1
Content PCP (CEN/TR14823)	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533 NPD
Thermal Conductivity (EN12664)	0,11 W/mK
Thermal Resistance R-Value	.10 (m2K/W)
Biological Durability (EN350-2.)	Class 1
CARB2	Compliant
Maximum installation area (floating)	15 x 25m (W x L)
Detail Description	Naturally occurring wood colour variations allowed, from light to dark brown. The product includes medium healthy and filled knots. Knots may vary in size and numbers. Patinates over time.



Wooden parquet flooring with 3,5 mm top layer and patented 5G[®] locking system for quick and easy installation.

RAW[®]

PARQUET FLOORING ASH 14MM RUSTIC WHITE, 3 STRIP, 5G[®], MATT



EAN	5710764671273
ART.nr	9752596
Overflademateriale	Ask
Overfladebehandling	Mat lak
Indfarvet	Hvid
Design	Nej
Sortering	Rustik
Låsesystem	5G [®]
Kernemateriale/bagside	Fyr / gran / el
Brættets tykkelse	14
Brættets overflade længde (mm)	2423
Brættets overfalde bredde (mm)	200
Slidlag tykkelse (mm)	3,5
Kan slibes	Ja
Stave	3
Brædder/pakke	8
kvm/pakke	2,91 m ²
Vægt/kvm (kg)	7,51 kg
Vægt/pakke (kg)	22 kg
Svanemærket	Ja
Made in	EU
Hårdhed (Brinell)	4
Gulvvarme	Ja, Max 27°C og 80W / m ²
Pakkeinformation	Kan indeholde start & stopbrædder
Moisture content (EN13183)	7% ±2%
Minimum Mean Density kg/m ³	>500 kg/ m ³
Reaction To Fire (EN1350-1)	Dfl-s1
Formaldehyde Emission (EN717-1)	E1
Content PCP (CEN/TR14823)	≤ 5 x 10 ⁻⁶ n
Breaking Strength N/mm ²	EN1533. NPĐ
Thermal Conductivity (EN12664)	0,11 W/mK
Thermal Resistance R-Value	.10 (m ² K/W)
Biological Durability (EN350-2.)	Class 1
CARB2	Compliant
Max areal for installation (svømmende)	(W)15m x (L)25m
Detaljeret beskrivelse	Naturlige farvevariationer må forekomme, fra lys til mørk brun. Splintved kan forekomme. Produktet indeholder middelstore, sunde og fyldte sorte knaster. Knaster kan variere i størrelse og antal. Patinerer over tid.



Wooden parquet flooring with 3,5 mm top layer and patented 5G[®] locking system for quick and easy installation.

01.2020_V1

RAW[®]

PARQUET FLOORING

ASH 14MM RUSTIC WHITE, 3 STRIP, 5G[®], MATT



EAN	5710764671273
ART.nr	900249014
Material ytskikt	Ask
Ytbehandling	Matt lack
Infärgad	Vit
Designinslag	Nej
Sortering	Rustik
Fog system	5G [®]
Material stomme	Fur / Gran / Al
Brädans tjocklek (mm)	14
Brädans längd, yta (mm)	2423
Brädans bredd, yta (mm)	200
Tjocklek slityta (mm)	3,5
Slipbar	Ja
Antal slitytor	3
Brädor/paket	8
Kvm/paket	2,91 m ²
Vikt/kvm (kg)	7,51 kg
Vikt/paket (kg)	22 kg
Svanencertifierad	Ja
Tillverkad i	EU
Brinell värde	4
Fungerar med golvvärme	Ja. Max 27°C och 80w/m ²
Paketinformation	får innehålla start/stop brädor
Fuktkvot (EN13183)	7% ±2%
Minsta medeldensitet kg/m ³	>500 kg / m ³
Brandklassning (EN1350-1)	Dfl-s1
Formaldehydutsläpp (EN717-1)	E1
Innehåll PCP (CEN/TR14823)	≤ 5 x 10-6n
Fogstyrka N/mm ²	EN1533. NPĐ
Värmeledningsförmåga (EN12664)	0,11 W/mK
Värmeledningsmotstånd	.10 (m2K/W)
Biologisk hållbarhet (EN350-2.)	Class 1
CARB2	Compliant
Maximal yta som kan läggas (flytande)	(W)15m x (L)25m
Detaljerad beskrivning	Naturliga färgskillnader är tillåtna, från ljus till mörkbrunt. Ytved kan förekomma. Sorteringen innehåller måttliga, friska och fyllda, kvistar. Kvistar varierar i storlek och antal. Färgförändras över tid



Wooden parquet flooring with 3,5 mm top layer and patented 5G[®] locking system for quick and easy installation.

01.2020_V1