

| DOP: Spaandex EN 312 P1                           |   |        |        |        |        |        |                      |
|---|---|--------|--------|--------|--------|--------|----------------------|
| 1. Type of materiel:                              | Particleboard acc. to EN 312 P1   |        |        |        |        |        |                      |
| 2. Unique identification code of the product-type | Spaandex EN 312 P1  |        |        |        |        |        |                      |
| 3. Intended use                                   | internal use dry conditions   |        |        |        |        |        |                      |
| 4. Manufactured at                                | Kronospan ApS<br>Novopan Træindustri<br>Fabriksvej 2, Pindstrup<br>DK-8550 Ryomgård |        |        |        |        |        |                      |
| 5. System of AVCP.                                | AVCP 2  |        |        |        |        |        |                      |
| 6. Notified Body                                  | Dancert A/S<br>Gregersensvej 4<br>DK-2630 Taastrup                                  |        |        |        |        |        |                      |
| 7. Declared performance<br><br>*: EN 321          | Thickness [mm]  | >8-13  | >13-20 | >20-25 | >25-32 | 32-38  | EN<br>13986:200<br>4 |
|   | Bending strength [N/mm <sup>2</sup> ]   | ≥ 10,5 | ≥ 10   | ≥ 10   | ≥ 10   | ≥ 8,5  |                      |
|   | Internal bond [N/mm <sup>2</sup> ]  | ≥ 0,40 | ≥ 0,30 | ≥ 0,30 | ≥ 0,30 | ≥ 0,25 | EN<br>312:2010       |
|   | Formaldehyde [mg/100g v. 6,5% fugt]   | ≤ 8    | ≤ 8    | ≤ 8    | ≤ 8    | ≤ 8    |                      |
|   | Reaction to fire  | Ds2-d0 | Ds2-d0 | F      | F      | F      |                      |

The performance of the product identified is in conformity with the declared performances.

---

Henrik Skovbo, laboratorie- og kvalitetschef

Pindstrup d. 16/10-2018