



DT-821852

UK: Data sheet

DOMESTIC Frost Guard 200W

Main specifications:

Rated power:	200W
Rated voltage:	220-240V
Rated frequency, Hz:	50-60HZ
The Housing:	Steel
Thermostat:	KST200, AC250V 16A 10E4,T100,Tf:85 EN60730-2-9,2003
Thermal cut-out, self-resetting:	KSD301, AC250V 16A 1E4,T160,Tf:135, EN60730-2-9,2004
Heating elements/tube:	AC220-240V;50-60HZ, 200W EN60335-2-30 2003
Colour:	WHITE / LIGHT GREY
Power plug:	AC250V,16A, DIN 49441-R2, Schuko
Power cord:	H05RN-F 3G0.75mm ² 1.6m(exposed) Material: Rubber
IPXX:	IP23
Insulation class:	Class I, earth needed
Stand or wall-mounted:	Wall-mounted only

DK: Datablad

DOMESTIC Frostvagt 200W

Specifikationer:

Nominel effekt:	200W
Nominel spænding:	220-240V
Nominel frekvensHz:	50-60HZ
Husning:	JERN
Termostat:	KST200, AC250V 16A 10E4,T100,Tf:85 EN60730-2-9,2003
Termiske sikring, selv-nulstillende:	KSD301, AC250V 16A 1E4,T160,Tf:135, EN60730-2-9,2004
Varmeelementer/rør:	AC220-240V;50-60HZ, 200W EN60335-2-30 2003
Farve:	HVID / LYS GRÅ
Strømsstik:	AC250V,16A, DIN 49441-R2, Schuko
Strømledning:	H05RN-F 3G0,75 mm ² 1,6 m (eksponeret) Materiale: Gummi
IPXX:	IP23
Isoleringsklasse:	klasse I, skal jordes
Stativ eller vægmonteret:	Kun vægmonteret

Data ark

DOMESTIC Frostbeskyttelse 200W

Hovedspesifikasjoner:

Nominell effekt:	200W
Merkespenning:	220-240V
Vurdert frekvensHz:	50-60HZ
Rammen:	JERN
Termostaten:	KST200, AC250V 16A 10E4,T100,Tf:85 EN60730-2-9,2003
Termiske utkoblingen, selvreduserende:	KSD301, AC250V 16A 1E4,T160,Tf:135, EN60730-2-9,2004
Varmeelementer/rør:	AC220-240V;50-60HZ, 200W EN60335-2-30 2003
Farge:	HVIT, LYS GRÅ
Støpsel:	AC250V,16A, DIN 49441-R2, Schuko
Strømledning:	H05RN-F 3G0.75mm ² 1.6m(utvendig) Materiale: Gummi
IPXX:	IP23
Isolasjonsklasse:	klasse I, jord nødvendig
Stativ eller veggmontert:	kun veggmontert

Datablad

DOMESTIC Frostvakt 200 W

Spesifikation:

Märkeffekt :	200 W
Märkspänning:	220–240 V
MärkfrekvensHz:	50–60 Hz
Hölje:	JÄRN
Termostat:	KST200, AC 250 V 16 A 10E4, T100, Tf:85 EN 60730-2-9, 2003
Värmsäkring, självåterställande:	KSD301, AC 250 V 16 A 1E4, T160, Tf:135, EN 60730-2-9, 2004
Varmeelement/tub:	AC 220–240 V; 50–60 Hz, 200 W EN 60335-2-30, 2003
Färg:	VIT, LJUSGRÅ
Strömkontakt:	AC 250 V, 16 A, DIN 49441-R2, Schuko
Strömkabel:	H05RN-F 3G0,75mm ² 1,6 m (synlig) Material: Gummi
IPXX:	IP23
Isolationsklass:	Klass I, jordning krävs
Stående eller väggmonterad:	Endast väggmontering

Tietolomake

DOMESTIC Frost Guard 200W

Tärkeimmät tekniset tiedot:

Nimellisteho:	200W
Nimellisjännite:	220-240V
Nimellistaajuus, Hz:	50-60HZ
Kotelo:	RAUTA
Termostaatti :	KST200, AC250V 16A 10E4,T100,Tf:85 EN60730-2-9,2003
Termaalinen automaattikatkaisin, itsenollaus:	KSD301, AC250V 16A 1E4,T160,Tf:135, EN60730-2-9,2004
Lämmityselementit/putki:	AC220-240 V;50-60 HZ, 200W EN60335-2-30 2003
Väri:	VALKOINEN, VAALEANHARMAA
Sähkötulppa:	AC250V,16A, DIN 49441-R2, Schuko
Sähköjohto:	H05RN-F 3G0,75 mm ² 1,6 m(paljastettu) Materiaali: Kumi
IPXX:	IP23
Eristysluokka:	luokka I, tarvitaan maadoitus
Lattialle seisova tai seinälle kiinnitetty:	ainoastaan seinälle kiinnitetty