

## Area of Application

ESSVE Drywall screw is designed for the application of plasterboards indoors against light steel joists, drill capacity 0.4 - 0.9 mm.

## Description

The screw is produced by hardened carbon steel with phosphated or bright zinc plated sur-

face. It is equipped with Philips crosshead Ph2.

## Installation

A screwdriver with a depth stop should be used for quick and efficient assembly.

Recommended rpm:  
25-50 mm 2800-6000/min.



## Specification

	Phosphated	Bright zinc plated
Material	Hardened Carbon steel SAE C1018	Hardened Carbon steel SAE C1018
Surface finish	Phosphated	Bright zinc plated 5 µm
Screw use	Approx 20 per m <sup>2</sup>	Approx 20 per m <sup>2</sup>
Corrosion class	C1	C1

## Drywall screw for steel joists, bright zinc plated ESSBOX



Item no.	Dimension dk x L mm	D mm	B mm	Bit no	ESSBOX size	Qty/pack.	Pack./large pack.
522625	3.5 x 25	8.4	20.0	PH2	202	250	12
522641	3.5 x 41	8.4	36.0	PH2	203	250	8
522650	3.5 x 50	8.4	45.0	PH2	203	200	8
522125	3.5 x 25	8.4	20.0	PH2	204	1000	6
522143	3.5 x 41	8.4	36.0	PH2	304	900	4
522150	3.5 x 50	8.4	45.0	PH2	304	500	4
522175	4.2 x 75	8.4	50.0	PH2	204	200	6

Art.nr	Dimension dk x L mm	RSK-nr	D mm	Antal per hink
522224	3,5 x 25		8,4	3500
522242	3,5 x 41		8,4	2000