

### Area of Application

ESSVE Drywall screw GU outside with drillpoint, is intended for installation of drywall boards outside on outer walls against steel joists. Drill capacity 0.7-2.0 mm.

### Description

ESSVE Drywall screw GU with drillpoint, is a newly developed screw with a flat surface-mounted head.

This design provides a weatherproof installation before the façade cladding is fitted.

The design of the screw conforms to the requirements set out in HusAMA 98 on the installation of outside drywall boards, KBC.111. The screw is fitted with a drillpoint, which makes it suitable for installing against steel joists

max. 2.0 mm.

The screw is made of hardened steel with silver CorrSeal surface treatment, making it suitable for use in outdoor environments. The silver CorrSeal surface treatment realises corrosivity category C4. Drywall screw GU combi is suitable for the most common autofeed screwdrivers available on the market.

### Installation

A screwdriver with adjustable depth stop should always be used to ensure correct, quick and efficient installation. The screw must not be countersunk, the surface finish of the board must not be damaged. Recommended rpm: 30 - 40 mm 2800 - 6000/min



**CorrSeal**

ESSVE CorrSeal surface treatment.



Type approved by SITAC No. 0075/05

### Specification

Material	Hardened steel SAE 1022
Surface treatment	CorrSeal, wax
Corrosion category	C4

## Drywall screw GU outside with drillpoint for steel joists, CorrSeal

### Technical data and packing

Item no.	Dimension dk x L mm	D mm	B mm	Bit no	Qty/pack.	Pack./large pack.
582325	3.5 x 25	9.0	21.0	PH2	1000	6
582340	3.5 x 40	9.0	36.0	PH2	1000	6

