



[print it](#)

Painted Hardboard

Hardboards may be painted in white. Painted board is coated with a layer of acryl UV varnish that increases its strength and resistance to exposure. Only modern board painting technologies are employed and clean, water-soluble paint, printing dye, and priming is used that is harmless to human health and environment friendly.



Application:

Painted hardboard is used for interior decoration of low-humidity residential, public, or industrial premises.

These boards are ideally suited for:

- Production of internal planes of furniture (cabinet internal walls, bottoms of drawers, beds and couches);
- Interior and exhibition planes (walls, exhibition components, decorations);
- Train car interior decoration, other consumer or industrial goods.

Physical-Mechanical Characteristics:

| Thickness (mm) | Thickness Tolerance (mm) | Density (kg/m ³) | Internal Cohesion (N/mm ²) | Swelling in 24 h (%) | Bending Resistance (N/mm ²) | Weight (kg/m ²) | Size (mm): |
|----------------|--------------------------|------------------------------|--|----------------------|---|-----------------------------|---|
| 3,2 | ± 0,3 | ≥ 900 | ≥ 0,5 | ≤ 35 | ≥ 30 | ~ 3,00 | 1220x2440, 1220x2745, 1220x3050, 1700x2745 |
| 2,5 | | | | | ≤ 35 | | |

Painted hard fiberboard in non-standard sizes is also available according to the customer's requirements.

Contacts:

Tel.: +370 5 243 5840

+370 5 243 5842

Fax.: +370 5 243 5846

E-mail: hardboard@baltwood.lt



www.baltwood.lt