

Nordsjö Perform+ Bathroom Primer

April 2018



Product description

Nordsjö Perform+ Bathroom Primer is a combination of binder and primer that is intended for wet rooms. It is a mould and mildew resistant primer with a light blue tint. Nordsjö Perform+ Bathroom Primer fully impregnates the textured wallpaper to which it is applied, resulting in a seamless, water-resistant surface with no pores.

Directions for use

Filler should be applied to plaster, concrete and other sheet materials wherever necessary using Nordsjö Professional Våtrum. After applying filler as needed, prime the wall with a mixture of Nordsjö Perform+ Bathroom Primer and water in a 1:1 ratio. After drying, Nordsjö Våtrumsväv (bathroom wallpaper) is hung using Nordsjö Perform+ Bathroom Primer. Wear cloth gloves to make the job easier. Immediately afterwards, apply primer to the wallpaper using Nordsjö Perform+ Bathroom Primer. After it dries, apply 2 coats of Nordsjö Perform+ Bathroom using a new roller. Allow the painted walls to dry for 7 days before exposing them to water. Do not paint if the temperature in the room below +10 °C.

Other

Nordsjö Perform+ Bathroom Primer is part of the Nordsjö wet room system, approved in accordance with the Swedish industry standard (MVK) for wet rooms.

Health and environment

When sanded or treated with a heat gun, coats of paint may give off dust and/or vapour that is hazardous to health. Work in a well-ventilated area. Use suitable personal protective equipment (respiratory protection) if insufficient ventilation is available. Please also read the Safety Data Sheet. Firmly reseal any opened cans. Remove paint from all tools (brushes, rollers, etc.) before cleaning. Immediately clean all tools after painting. Do not flush liquid paint residues or cleaning solvents down the drain. Take them to your nearest waste/recycling centre. Packaging should be submitted for recycling.



Technical data

Typical use: Interior
Binder: Acrylic copolymer dispersion
Gloss: Blank (glossy)
Drying time 23°C 50% RH: Touch dry after 5 hours, Recoat after 7 hours
Application temp: Min. +5°C
Humidity RH: 40-80% RF (65% RF is optimal)
Thinning: Water
Tools: Brush, roller, spray
Paint consumption: 2-5 m²/lit
Package sizes: 1L, 2.5L and 10L
Bases: Blue tint
Cleaning: Soapy water:
Storage: Frost-free
EU VOC limit value (Cat. A/b) 100g/l
Contains Max 35g/l

AkzoNobel

AkzoNobel Decorative Coatings AB. Tel. +46 (0) 40 35 50 00

The data sheets are issued for advisory purposes only. The values are applicable to normal circumstances and may therefore vary depending on the application method, temperature, etc. We reserve the right to make changes without prior notice. The user is responsible for ensuring that the latest version of this document is used. It is possible to check this on our website.
AkzoNobel and Nordsjö are trademarks of the AkzoNobel Group of Companies © AkzoNobel 2009