

# Area of Application

ESSVE Moulding, board screw designed for installing boards indoors on wooden or steel joists. Drill capacity 0.4 – 0.9 mm.

### Description

The screw is produced in hardened carbon steel with bright zinc plated, yellow chromate surface treatment or yellow chromate with white painted head, (RAL 9010). Fitted with Philips crosshead Ph2.

The head is equipped with cutting grooves that countersinks the screw, leaving a smooth surface without splinters.



### Installation

Recommended rpm: 400-1200/min.

### Specification

	Yellow chromate	Yellow chromate/white finish
Material	Hardened steel SAE C1018	Hardened steel SAE C1018
Surface treatment	Yellow chromate 5 µm	Yellow chromate 5 µm/white pain- ted head (RAL 9010)
Corrosion categories	C1	C1

# Moulding/base screw for wooden and steel joists, yellow chromate ESSBOX

# 

	Dimension dk× L mm	D	в	Bit	ESSBOX	Qtv/	Pack./ large
Item no.		mm	mm	no	size	pack.	pack.
557145	3,4 × 45	6,2	23,0	PH2	202	250	12
557155	3,4 × 55	6,2	23,0	PH2	204	250	6

## Small package

	Dimension					Pack./
	dk x L mm	D	В	Bit	Qty/	large
Item no.		mm	mm	no	pack.	pack.
413500	3,4 × 45	6,2	23,0	PH2	100	6
413502	3,4 × 55	6,2	23,0	PH2	100	6